


## UPG-P200 50 Hz



### POWERED BY



Three phase



water cooled



DIESEL



Battery Charging Alternator

### Ratings @ 0.8 PF

VOLTAGE	FREQUENCY	PRIME RATING		STAND-BY RATING	
230/400 v	50 Hz	200.0 kva	160.0 kw	220.0 kva	176.0 kw

### Prime

These ratings are applicable for supplying continuous electrical power (at variable load). There is no annual hours limitation and this genset can supply 10% overload for 1 hour in 12 hours

### Stand by

These ratings are applicable for supplying continuous electrical power(at variable load) in the case of emergency power supply. No overload is permitted on the ratings.  
The alternator on this model is peak continuous rates(as defined in ISO 8528-5)

Some of the specifications are not standard on all Genset models.

### Genset Standard Specification

Model	UPG-P200
Base frame	Heavy duty fabricated steel
Circuit breaker	ABB 3 pole MCCB(4 pole is optional)
Engine speed	1500 RPM(50HZ)
Fuel tank capacity(L)	261 - open 255(403) - closed
Air inlet	Mounted air filter
Induction system	Turbo charged and air to charge cooled
Combustion system	Direct injection
Fuel system	Fuel injection pump
Fuel filter	Split element
cooling system	Water-cooled
Electric Equipment	12 v starter motor and 12 v DC alternator and 12 v shut off solenoid

Genset Model

UPG-P200

Engine Model


Perkins 1106A-70TAG4

Alternator Model

TAL 044 L / TAL 044M

Controller Model

DSE 6120



### Dimension

Closed type(mm)		Open type(mm)	
Length	3200	Length	2500
Width	1100	Width	775
Height	1650	Height	1425
Weight(kg)	1990	Weight(kg)	1630

### Engine Data

Model	Perkins 1106A-70TAG4	
No of cylinder & arrangement	6 vertical in-line	
Compression ratio	18.2:1	
Aspiration	Turbo charged after cooled	
Bore and stroke(mm)	105 x 135	
Displacement / Cubic Capacity litres	7.01	
Rotation	Anti-clockwise, viewed on flywheel	
Governor	Electronic	
Radiator cooling air flow(m³/sec)	4.7	
	50 Hz	
	Prime	Stand by
Gross engine power kw(hp)	184(247)	202(271)
at 50% Load(l/hr)	23.1	-
at 75% Load(l/hr)	34.7	-
at 100% Load(l/hr)	45.8	49.4
Total lubrication system capacity(L)	18.0	18.0
Total Coolant capacity(L)	21.0	21.0

### Alternator Data

Make	Leroy Somer TAL / Equivalent	
Model	TAL 046B / TAL 044M	
Insulation class	H	
No of bearing	1	
Total harmonic content	at no load <2.5% / <2% at linear load <5% / <5%	
Winding pitch	2/3	
Ingress Protection	IP23	
Altitude	≤1000m	
Overspeed	2250 R.P.M	
AVR Model	R150	
Excitation system	SHUNT	
Voltage regulation(steady)	± 0.8% / ± 1%	

AREP or PMG Excitation System Available as Optional

All information in this document is substantially correct at time of printing and may be altered subsequently.

matte black coated Stainless  
Steel Lockable handles

Control Panel  
managed by DSE 6120



insulation

Sound proof  
galvanised  
canopy

daily fuel tank in base frame  
for 8 h operation

forklift pocket  
for safe handling



## Enclosure

### SILENT FEATURES:

- Lockable external fuel filling point
- Internal /External fuel connection
- External oil drainage
- External coolant drainage
- Air inlet /outlet louvers
- Sound splitters at radiator side (only for 1000 KVA and above) (For 725-880 KVA vertical air discharge)
- Common earth connection
- powder coated galvanized canopy
- Cooling fan and battery charging alternator fully guarded
- Engine, radiator, fuel fill and battery can only be reached via lockable access doors

### HIGLY CORROSION RESISTANCE CONSTRUCTION

- Carbon steel locks and hinges
- Body made from galvanized steel components
- treated with polyester powder coating

### TRANSPORTABILITY

- Tested and certified single point lifting facility
- Forklift legs available

### SOUND PRESSURE LEVEL

- 80 - 85 dBA at 3 meters (standard)

### SECURITY AND SAFETY:

- Control panel viewing window in a lockable access door
- Emergency stop push button (red) fixed externally for quick access
- Cooling fan and battery charging alternator fully guarded
- Fuel fill and battery can only be reached via lockable access doors
- Exhaust silencing system totally enclosed for operator safety

### Control Panel Data

Make	Deep Sea
Model	DSE 6120 MKII



## Controller key features

The DSE DSE 6120 is an Auto Start Control Module for single genset applications. It includes a backlit LCD display which clearly shows the status of the engine all the times. This module can either be programmed using the front panel or by using the DSE configuration suite PC software.

### Metering and Alarm indications:

- Generator frequency
- Underspeed, Overspeed
- Generator volts (L-L, L-N)
- Generator current
- Engine oil pressure
- Engine coolant temperature
- Hours run counter
- Battery volts
- Fail to start/stop
- Emergency stop
- Charge fail
- Low DC voltage

### FUEL SYSTEM

On Generating Sets up to 700 KVA, the baseframe design is incorporated with an integral fuel tank with a capacity of approx. 8 hours running at Full Load. The tank is supplied complete with fill cap breather, fuel feed and return lines to the Engine and drain plug.

Silencer noise reduction level	50 Hz
dBA	12
Max allowable pressure	50 Hz
Kpa	6
Exhaust gas flow m <sup>3</sup> /min	50 Hz
Prime	34.9
Standby	36.8
Exhaust gas temperature °C	50 Hz
Prime	550
Stand by	550

### AUTOMATIC VOLTAGE REGULATOR (AVR)

The fully sealed Automatic Voltage Regulator maintains the Voltage Regulation at ±1%. Nominal adjustment by means of a trim pot incorporated on the AVR.

### MOTOR STARTING

An overload capacity equivalent to 300% of the Full Load impedance at zero Power Factor can be sustained for 10 seconds, when PMG option is fitted.

### COUPLING

The Engine and Alternator are directly coupled by means of an SAE flange. The Engine flywheel is flexibly coupled to the Alternator rotor.

### ANTI-VIBRATION MOUNTING PADS

Anti-Vibration pads are affixed between the Engine / Alternator feet and the Baseframe thus ensuring complete vibration isolation of the rotating assembly.

### SAFETY GUARDS

The Fan & Fan Drive along with the Battery Charging Alternator are Safety Guard protected for personnel protection.

### FACTORY TESTS

The Generating set is load tested before dispatch All protective devices control functions and site load conditions are simulated. The generator and it's systems are checked before dispatch.

## DOCUMENTATIONS

Operation & Maintenance manual, Circuit wiring diagrams and Commissioning / Fault Finding accompanied with the Generator.

## QUALITY STANDARDS

Following standards: ISO 8528/1, ISO 3046/1, BS 5514/1.

## WARRANTY

All of the Generating Sets are covered under a warranty policy for a period of 12 months. Warranty of the equipment is in line with manufacturers warranty terms & conditions.

All information in this document is substantially correct at time of printing and may be altered subsequently.